

PRV

PATENT- OCH REGISTRERINGSVERKET
Patentavdelningen

10532790

DT01 Rec'd PCT/PTC 25 APR 2005

Intyg Certificate

Härmed intygas att bifogade kopior överensstämmer med de handlingar som ursprungligen ingivits till Patent- och registreringsverket i nedannämnda ansökan.

This is to certify that the annexed is a true copy of the documents as originally filed with the Patent- and Registration Office in connection with the following patent application.



(71) Sökande St Jude Medical AB, Järfälla SE
Applicant (s)

(21) Patentansökningsnummer 0203220-9
Patent application number

(86) Ingivningsdatum 2002-10-31
Date of filing

Stockholm, 2003-06-02

För Patent- och registreringsverket
For the Patent- and Registration Office

Hjordis Segerlund

Avgift
Fee 170:-

Motion sensor

Technical field

5 The invention concerns a motion sensor for measuring a patient's activity level comprising a fluid-tight, bio-compatible housing, a plurality of electrodes being coupled to the housing and the housing comprising a fluid. Furthermore, the invention relates to an implantable medical device, such as a heart stimulator, e.g. cardiac pacemaker comprising the motion sensor.

10

Prior art

Heart stimulators, below exemplified by pacemakers are used to e.g. pace the frequency of the heart. They have been of greatest importance for helping individuals suffering from various heart diseases and/or failures to live rather normal lives.

15

Pacemakers function by generating electrical pulses, which stimulate the heart. In order to pace the heart in a correct way, the specific pulse pattern of the individual heart must be known. External parameters, such as the motion of the patient, are advantageously known, in order for the pacemaker to stimulate the heart as correctly as possible.

20

Normally, the motion of the patient is measured by some kind of motion sensor, which sensor is connected to the pacemaker. US-A-5755741 discloses an implantable sensor providing an indication of movement and orientation of a patient.

25

The sensor may be connected to a pacemaker. The sensor comprises a cylindrical enclosure having a central electrode within a cavity of the enclosure, and one or more peripheral electrodes within the cavity. An electrolytic fluid is positioned in the enclosure so that movement of the sensor results in variations of the amount of the fluid between the central electrode and one or more of the peripheral electrodes.

An alternating current applied to the electrodes will render a voltage signal, which varies in accordance with the movements of the fluid (and the sensor).

5 US-A-5833713 discloses an accelerometer-based, multi-axis physical activity sensor for use with a rate-responsive pacemaker. A piezoelectric polymer film is adhered to the surface of an electrically conductive substrate on the sensor. In response to bodily accelerations the piezoelectric film produces an output signal.

10 US-A-5233984 discloses a multi-axis sensor, for example connected to a pacemaker, for measuring a patient's activity level. The sensor comprises a hermetically sealed, fluid-tight, biocompatible housing, whereby a plurality of electrodes is coupled to the sides of the housing, and a central electrode is positioned within the housing. An electrically conductive electrolyte fills about half of the housing, allowing voltage changes, due to motion of the sensor, between the central electrode
15 and the other electrodes to be monitored.

Also, US-A-4869251 discloses a pacemaker having a sensor for detecting inertial and/or rotational movements of a patient. The sensor has a hollow member, with at least one freely moveable member therein generating a mechanical vibration upon
20 movement of the patient. A transducer generates an electric signal corresponding to the mechanical vibrations. It is stated that the hollow member may be filled with a fluid and/or a plurality of particles producing pressure to the walls of the hollow member. It is also stated that the sensitivity of the sensor may be different in different directions. For example, the moveable element may be a magnetic dipole, and
25 the transducer may be one or more coils arranged around the hollow member, whereby a current is generated in the coils when the moveable element changes position in the interior of the hollow member. Depending on configuration, the mobility of the movable element may however degrade due to mechanical wear.

Accordingly, the motion sensors of the prior art normally rely on moving mechanical components, and therefore they may be difficult to miniaturise further. This is a problem, since the size of the motion sensor (and pacemakers) advantageously is as small as possible, in order to disturb the biological system into which they are put as little as possible. Furthermore, as mentioned above, mechanically based sensors may suffer from mechanical wear, which can lead to their failure.

Accordingly, it is an object of the present invention to provide a motion sensor, which overcomes the drawbacks of the prior art, and thereby comprises as few mechanical parts as possible, the sensor further being as small as possible, and relying on a technical principle making it as resistant to failure as possible.

Summary of the invention

These and other objects are accomplished by a motion sensor according to claim 1 of the present invention, which relies on the principle of an electrically detectable anisotropic fluid, which fluid orients itself in relation to external motion.

Hereby, a sensor is provided in which no moving parts are comprised, and which therefore is possible to make very small.

In a preferred embodiment, the anisotropic fluid comprises long rigid LCP-molecules, on which electrically detectable magnetic nanoparticles are covalently linked.

In another embodiment a magnetic field is applied to the anisotropic fluid, and the alignment of the anisotropic molecules is detected by measuring the capacitance of the fluid.

Moreover, the invention relates to an electrically detectable anisotropic fluid comprising a liquid crystalline polymer (LCP) as the anisotropic fluid, which LCP is covalently bound to an iron-oxide nanoparticle. This fluid is specifically suitable for use in the motion sensor of the invention.

5

Furthermore, the invention relates to an implantable pacemaker comprising the motion sensor of the invention. Hereby, a patient's heart is paced as a response to the patient's motion, as sensed by the motion sensor of the invention.

10

Accordingly, the drawbacks of the prior art are overcome.

Short description of the drawings

15

Figure 1 shows a principal sketch of a motion sensor according to one embodiment of the invention.

Figure 2 shows a principal coupling scheme for a motion sensor of the invention coupled to a rate response pacemaker.

20

Preferred embodiments

25

The idea of the invention is to provide a motion sensor, especially adapted for use with a pacemaker, which is as small as possible, and which circumvents the problem of mechanical wear in a sensor comprising several mechanical parts. This is provided by a sensor, which relies on the principle of an anisotropic fluid or an anisotropic molecule within a fluid. Thereby, the only moving parts of the sensor are fluids.

30

Accordingly, in a first aspect the invention relates to a motion sensor for measuring a patient's activity level comprising a fluid-tight, bio-compatible housing, a plurality

of electrodes being coupled to the housing, the housing comprising a fluid that comprises at least one anisotropic molecule, the anisotropic properties of which are changed in relation to the motion of the fluid, whereby the state of the anisotropic molecules of the fluid is detectable by the electrodes.

5

In a preferred embodiment, the motion sensor is implantable in the patient in question. However, the motion sensor may also be adapted for external use, i.e. not being implanted in the body of the patient, but communicating by for example some telemetric means with an implanted pacemaker.

10

By a "patient" is in the context of the invention meant an animal, especially a human, which is in need of a motion sensor. This may for example include persons which have a pacemaker or whom is to be equipped with a pacemaker. However, the motion sensor of the invention must not necessarily be coupled to a pacemaker, but may also be connected to any other device or circuitry for which the output of the motion sensor is relevant.

15

By a patient's "activity level" is meant the degree of motion for the specific patient. For example, for a pacemaker to deliver the correct pulses to a patients heart, it is important to correlate these pulses with the "activity level" of the patient, in order for the pacing pulses and the resulting heart responses to be suited for the patients present need. Thus, it is preferred that the paced heart rate is adaptable to different levels of exertion by the patient.

20

By "a plurality of electrodes " is meant at least one electrode pair, having the capacity to monitor at least one electronic parameter.

25

An anisotropic molecule will orient itself in relation to the motional stress it is subjected to. Thus, for example, an anisotropic molecule may exhibit anisotropic properties at rest and isotropic properties when agitated (i.e. different states). Accord-

30

ingly, a plurality of molecules of this kind will, like a crystal, align in a common direction at rest, or in a laminar shearing force. The viscosity, as well as several other physico-chemical properties, such as optical transmission, heat transfer, polarity, conductivity etc., will then be very different in the alignment direction compared to other directions, especially the perpendicular direction. However, if agitated, the molecular alignments will become randomised, and as a result properties such as viscosity or dielectric constant will be practically equal in all directions. Thus, when a patient carrying the sensor of the invention moves, the sensor will sense these movements (or lack of movements) and create an output signal, which is based on them.

Liquid crystalline polymers (LCP's)(Langmuir 2001, 17, 2900-2906) are fluids having anisotropic properties at rest and isotropic properties during agitation. LCP's, in the context of the invention, are long rigid molecules, which have an aspect-ratio (length/diameter) of greater than about (10/1). One example, which is suitable for the purposes of the invention, is poly-(p-phenylene) with a degree of polymerisation (n) equal to or greater than 10. In this context, the aspect-ratio would be a more relevant term than for example molecule length, since a rigid rod polymer with a wide diameter will not exhibit anisotropic properties at the same length or degree of polymerisation as a rigid rod polymer with a narrow diameter. The aspect-ratio, however, provides a good way to measure the intrinsic anisotropy of the polymer molecules.

Thus, according to one embodiment of the invention the anisotropic molecule is a liquid crystalline polymer (LCP).

Some other examples of liquid crystalline polymers suitable for the invention are given below. However, this list is not exhaustive, and other compounds may also be used.

A copolymer of p-hydroxybenzoic acid and polyethylene terephthalate. (Japanese Patent Publication No. 18016/1981); a copolymer of p-hydroxybenzoic acid, polyethylene terephthalate, aromatic diol (such as 4,4'-dihydroxybiphenyl), and aromatic dicarboxylic acid, with improved flowability and heat resistance. (Japanese Patent Laid-open No. 30523/1988); a copolymer of p-hydroxybenzoic acid, 4,4'-dihydroxybiphenyl, t-butylhydroquinone, and terephthalic acid. (Japanese Patent Laid-open No. 164719/1987); a copolymer of p-hydroxybenzoic acid, 4,4'-dihydroxybiphenyl, isophthalic acid, and terephthalic acid. (Japanese Patent Publication No. 24407/1982 and Japanese Patent Laid-open No. 25046/1985); a copolymer of p-hydroxybenzoic acid and 6-hydroxy-2-naphthoic acid. (Japanese Patent Laid-open No. 77691/1979); copolyesters of terephthalic acid, alkylhydroquinone, p-hydroxybenzoic acid and poly(alkylene terephthalate), the alkylene substituent preferably comprising ethylene or butylene and the alkyl substituent of the hydroquinone preferably comprising a lower alkyl group such as propyl or (tertiary) butyl; copolyesters of p-hydroxybenzoic acid and poly(alkylene terephthalate), the alkylene group preferably being ethylene or butylene; copolyesters of terephthalic acid, alkylhydroquinone, p-hydroxybenzoic acid and hydroxyalkylphenyl-alkanoic acids, the alkyl-substituent of the hydroquinone preferably comprising a lower alkyl group such as propyl or (tertiary) butyl, the alkanoic acid preferably containing 3 to 8 carbon atoms, propanoic acid being particularly preferred, and blockcopolyesters of trimellithic imide-terminated poly(THF) or polysilicone, containing the imide group in para- or meta-position i.e. N-(4-carboxy-phenyl)-trimellit imide or N-(3'-acetoxy-phenyl)-trimellit imide, with acetoxybenzoic acid and at least one repeating unit selected from the group comprising diacetoxy diphenyl, hydroquinone diacetate, terephthalic acid, a trimer designated HBA--HQ--HBA (the synthesis of which is described in Europ. Polym. J. 20, 3, 225-235 (1984), and poly(ethylene terephthalate) (PET).

The molecular weight of the liquid crystal polymer used in the present invention depends on the character of the repeating units of the LCP. Usually, the molecular

weight is in the range of about 1,000 to 300,000. If fully aromatic polyesters are used as LCP's, their molecular weight is typically in the range of about 2,000 to 200,000, preferably about 10,000 to 50,000.

5 More general details on liquid crystalline polymers and their properties and applications are given in an article titled "Liquid Crystal Polymers and Their Applications" by Chung et al. in Handbook of Polymer Science and Technology, Vol. 2 (1989) 625-675.

10 In order to be able to detect the anisotropic properties one may for example attach a doping agent to the anisotropic molecule, which doping agent have the capacity to provide a readable electronic signal. Thus, the doping agent constitutes an electrically detectable part. Hereby, a patient's activity level is possible to monitor.

15 The doping agent is coupled to the LCP-molecule by any common chemical bonding technique. Preferably, the doping agent is coupled to the LCP-molecule by covalent bonding. The skilled person in the art easily recognises techniques for binding the doping agent to the LCP, e.g. by hydrosilylation reactions using organosilane intermediates, for example dimethylvinyl silane.

20

Therefore, according to another embodiment the anisotropic molecule comprises an electrically detectable part.

25

The production of silica-coated iron oxide nanoparticles is described in the reference article Langmuir, Vol 17, No. 10, 2001 (2900-2906). Basically, they are produced in solution from appropriate chemical reagents, aided by suspension in organic surfactants. The particles are treated with tetraethylorthosilicate (TEOS) to form a silica coating. These particles are magnetic, and can be bound to an isotropic (rigid rod) molecule using covalent bonding and standard silica surface treatment chemistry, for example by silanization with dimethylvinyl silane. In one embodiment

30

of the present invention, the silane group bonds to the silica surface, and the vinyl group can form a covalent bond with many different kinds of organic molecules, including Liquid Crystalline Polymers (LCP's) containing dipoles. Under a small magnetic field (B), such as greater than about 0.5 Gauss, a preferential orientation will be induced, so that the magnetic particles line up in the magnetic field. The degree of alignment is preferably detected by measurement of capacitance across the fluid. The tendency for alignment is dependent on agitation because the dipoles will be forced by the magnetic particles to line up in the preferential orientation, but that orientation is disturbed by fluid motion.

For a principal sketch of one embodiment of the motion sensor of the invention see figure 1. The sensor 10 comprises a housing 11, which is filled by a fluid. The fluid comprises at least partly anisotropic molecules of the invention. Furthermore, a magnetic field is generated by the magnets 14 and 15. A capacitor 12 and 13 measures the capacitance of the fluid, and thus a variation in the anisotropic status of the fluid is monitored.

Examples of doping agents are ions or molecular dipoles. Preferably, a magnetically aligned nanoparticle (Langmuir 2001, 17, 2900-2906), or a charge-separated ion-pair, such as a zwitterionic pair (positive charge at one end, negative at the other) is used. The nanoparticle is in a preferred embodiment an iron-oxide nanoparticle, wherein iron-oxide may be represented by e.g. Fe_3O_4 , or $\gamma\text{-Fe}_2\text{O}_3$ (Langmuir 2001, 17, 2900-2906)

Thus, in yet another embodiment of the invention the detectable part is a magnetic nanoparticle, a zwitterionic pair or a charge separated ion-pair, preferably a magnetic iron-oxide nanoparticle.

Hereby, the electrical/magnetic signature is representative of the degree of alignment of the LCP's. As a consequence, the amount of agitation (i.e. patient activity)

is correlated to the electrical or magnetic signal, which the sensor and/or pacemaker circuitry is designed to detect. As a result a motion sensor having no moving parts (except the anisotropic fluid) and that can be made very small can be manufactured. For example, the sensor may have a cavity volume of a few mm^3 or less, such as less than 10 mm^3 , preferably less than 5 mm^3 , most preferably less than 1 mm^3 .

The suitable electronic signal to be monitored may vary depending on the nature of the system and its chemical content. However, for many applications measure of capacitance is suitable. In other cases measurement of voltage, voltage changes, impedance or resistance may be suitable.

Thus, in still another embodiment the state of the anisotropic molecule is monitored by measuring the capacitance in the fluid.

In yet another embodiment the state of the anisotropic molecule is monitored by measuring the resistance in the fluid.

In yet another embodiment, coils are arranged around the housing. Upon a variation in the state of the anisotropic fluid, a voltage is induced in the coils, which voltage is used as a signal. For example, the coil may be of insulated silver/copper wire.

The nanoparticulate size of the anisotropic entity molecules enables low enough viscosity that no moving parts (other than fluid) is necessary, even in small devices like a pacemaker. A half-empty cylinder is one preferred example of the container.

This container preferably has a magnetic N and a magnetic S pole provided by placement of permanent magnets 14 and 15 on opposite sides of its diameter. The electric sensor (e.g. capacitor electrodes 12 and 13) may also be on opposite sides of the cylinder diameter, though preferably normal (90 degrees) to the magnetic diameter (see figure 1).

It is not required to have the capacitor electrodes normal to the magnetic field, but it provides the optimum signal output. Each molecule of the fluid will act as a dipole with a dipole moment in a particular direction. When in a magnetic field, the dipole moments will tend to align in due to being bound to the magnetic particles as described in the reference article. The net dipole moment of the fluid is then finite and detectable as capacitance between the capacitance electrode. This "high order state" is detectable across any plane of the fluid except that parallel to the magnetic field, since in the parallel plane the LCP molecule ends face the electrodes and the LCP fluid would appear to the sensor to be small molecules with no preferable orientation in that plane. Therefore, in the "high order state", the signal is obtained as long as the capacitor electrodes are not in the parallel plane, a detectable signal in any other plane, and an optimum signal is obtained in the perpendicular plane. Note that when agitated, the dipoles become randomly oriented yielding a much lower net dipole moment - this "low order state" gives the same signal output independent of orientation between the capacitor electrodes and the magnetic field. So to achieve the maximum difference between the "at rest" state (high order) and the active state (low order), perpendicular is the preferred set-up, but sensitive electronics means that any orientation other than parallel to the magnetic field suffices.

However, in yet another embodiment the invention refers to an anisotropic molecule showing a specific dipole moment even in the parallel plane.

In the invention, air is preferably used as the agitating medium. However, it is also possible to have a completely filled cavity if it is ensured that the anisotropic fluid is agitated with body motion (note, it is fluid agitation that results in its altered properties). One such embodiment is a flexible housing completely filled, whereby the motion of the housing provides the agitation. Another embodiment would be to have a completely filled cavity containing inert particles in the fluid, which agitate the fluid with body motion (kind of like the ball bearing in spray-paint cans). If air is the agitator (which is preferred), 98% fluid is a reasonable upper limit. As a lower

limit, enough fluid to fill out the space between electrodes (preferably capacitor plates) is needed, which would necessitate a lower limit of about 20% fluid.

It is important that the sensor is implantable in the human body. For this to be readily made, the sensor is preferably constructed of bio-compatible material. Furthermore, since the housing of the sensor comprises a fluid, it is important that the housing is entirely fluid-tight, in order to secure the function of the sensor as well as the well being of the patient.

The housing may for example consist of glass, ceramic, plexiglass, thermoplastic, curable plastic, metal, rubber (for example silicone rubber) or any other suitable material. Also, the housing may be of any conventional structural biocompatible dielectric material, such as ceramic, phenolic resin, epoxy resin or polysulfone. The shape of the housing may for example be spherical, cylindrical, cubical, of a horse-shoe-shaped annulus form, or any other functional shape.

In one embodiment, the housing is configured in the shape of a cube having six sides, and the electrode includes six generally identical rectangularly shaped side electrodes. Each of these side electrodes is coupled to one side of the housing. The electrodes are electrically accessible outside of the sensor via conventional feed-throughs.

The electrodes can assume different shapes, such as a rectangle, a circle, a triangle, a parabola, or such other geometric shapes that will enable the mapping of the voltages, voltage changes, impedances and impedance changes between various reference points on the side electrodes.

These side electrodes are composed of conventional conductive material such as stainless steel or titanium. The side electrodes may be supported remotely by feed-

through connector wires or may be connected to the side via an insulator.

In still another embodiment the housing comprises means for creating shear forces in the anisotropic fluid by using a solid mechanical moveable element, such as a
5 bead or a ball made of non-ferromagnetic metal.

The sensitivity of the sensor can be varied by varying the concentration of the anisotropic molecule in the fluid.

10 The sensitivity of the sensor may also be varied by varying the viscosity of the fluid in the housing.

In a second aspect, the invention refers to an electrically detectable anisotropic fluid comprising a liquid crystalline polymer (LCP) as the anisotropic fluid, which LCP is
15 covalently bound to an iron-oxide nanoparticle. Hereby, a fluid is provided which is specifically adapted for use in a motion sensor of the invention.

In a third aspect, the invention relates to an implantable cardiac pacemaker comprising the implantable motion sensor described above, and means for pacing a
20 heart, such as a pulse generator, as a response to the activity level as detected by the motion sensor, which means is connected to said motion sensor. The physical activity of the patient in which the pacemaker is implanted is monitored using the sensor, and the output signal of the sensor is used to control the frequency of the pulse generator.

25 In an alternative embodiment of this aspect, the pacemaker does not comprise the motion sensor of the invention, but means for receiving signals from an external motion sensor. In this case, the external motion sensor communicates by means of telemetry or the like with the pacemaker.

By "implantable pacemaker" is meant that the pacemaker in question must be possible to implant in a patient, and thus the pacemaker should be constructed of for example biocompatible material.

5 By "means for pacing a heart" is meant any kind of conventional pacemaker or pulse generator, such as Microny® or implantable cardiac defibrillators comprising such means. The skilled person in the art would know suitable devices for use for this purpose.

10 In one embodiment, the sensor forms an entirely self-contained system within the heart pacemaker, which requires no additional external detectors or line connections outside of the heart pacemaker housing.

In another embodiment, the sensor could be implanted independently, remotely
15 from the implanted medical device. Yet another alternative would be to have the patient wear the sensor externally, such that the output signals from the sensor are transmitted by telemetry to the implanted medical device.

In any case, the sensor should be as small as possible, e.g. to allow incorporation
20 into an implantable pacemaker, preferably 0.5 cm square, or less.

In a preferred embodiment the output signal is capacitance, which must first be converted to a voltage signal. The sensor response frequencies need to be calibrated to correspond with appropriate patient motion frequencies.

25 The use of a sensor of the present invention in combination with control circuitry for a heart pacemaker may be as follows (figure 2): The sensor 20 according to this embodiment of the invention comprises a fluid, whose properties of dielectric permittivity change when agitated, causing a corresponding change in the capacitance
30 between two electrodes (as described above). The variable capacitance is used as an

input signal to 21. 21 is an oscillator, which yields an output frequency that depends on the capacitance input. The frequency generated by 21 is processed and converted to an appropriate signal in 22 (frequency-to-activity-signal conversion), as known in the art. The signal from 22 combined with input of a programmable target rate 31 are further processed in 23 (reaction and recovery circuit) to ensure appropriate reaction time and recovery time of the stimulation to the detected activity signals. The remainder of the flow diagram 24 (pacemaker logic circuit) through 28 are standard and is easily understood by the skilled person in the art of rate-responsive cardiac pacing (25 refers to an output circuit, 26 to an ECG (electrocardiogram) filter and amplifier, 27 to a refractory unit, and 28 to a timer for highest inhibited rate). The total circuit is coupled to the heart 30 of a subject between the output circuit 25 and the ECG filter and amplifier 26. The skilled person in the art would know the various components of the pacemaker circuit. Reference is made to e.g. US-A-5233984 and to Lindgren and Jansson, "Heart Physiology and Stimulation, an introduction", 1992, Siemens-Elma AB, Solna, Sweden.

The control signal for the heart pacemaker may be generated in digital form instead of the analog format discussed above. Digital processing can be undertaken in a microprocessor. In both cases, the programming can be done via a telemetry connection between the heart pacemaker and an external programming means.

In one embodiment of the invention a low/high frequency band pass filter (for measuring a patient's posture and activity) is used. This filter should preferably be calibrated, since the fluid properties of the fluid of the sensor will affect sensor response frequencies. Filtering frequencies may therefore need adjustment.

Claims:

1. Motion sensor (10, 20) for measuring a patients activity level comprising a fluid-tight, bio-compatible housing (11), a plurality of electrodes (12) being coupled
5 to the housing, the housing comprising a fluid **characterised by** that the fluid comprises at least one anisotropic molecule, the anisotropic properties of which are changed in relation to the motion of the fluid, whereby the state of the anisotropic molecules of the fluid is detectable by the electrodes.
2. Motion sensor according to claim 1, which motion sensor is implantable
- 10 3. Motion sensor according to claim 1 or 2, wherein the anisotropic molecule is a liquid crystalline polymer (LCP).
4. Motion sensor according to claim 3, wherein the LCP is poly (p-phenylene) having a degree of polymerisation (n) higher than or equal to 10.
5. Motion sensor according to any one of the preceding claims, whereby the aniso-
15 tropic molecule comprises an electrically detectable part.
6. Motion sensor according to claim 5, whereby the electrically detectable part is covalently coupled to the anisotropic molecule.
7. Motion sensor according to claim 5 or 6, wherein the electrically detectable part is a magnetic nanoparticle, a zwitterionic pair or a charge separated ion-pair.
- 20 8. Motion sensor according to claim 7, whereby the magnetic nanoparticle is an iron oxide nanoparticle.
9. Motion sensor according to any one of the preceding claims, whereby an external magnetic field (14, 15) is applied to the housing.
10. Motion sensor according to any of the preceding claims, whereby the state of the
25 anisotropic molecule is monitored by measuring the capacitance in the fluid.
11. Motion sensor according to claim 1-9, whereby the state of the anisotropic molecule is monitored by measuring the resistance in the fluid.
12. Motion sensor according to claim 10, whereby a pair of capacitance electrodes (12, 13) is positioned perpendicular to the applied magnetic field (14, 15).

13. Motion sensor according to any one of claim 1-12, whereby the housing comprises means for creating shear forces in the anisotropic fluid.
14. Electrically detectable anisotropic fluid comprising a liquid crystalline polymer (LCP) as the anisotropic fluid, which LCP is covalently bound to an iron-oxide nanoparticle.
15. Implantable cardiac pacemaker comprising the motion sensor of claim 1-13, or means for receiving signals from an external motion sensor, and means for pacing a heart, as a response to the activity level as detected by the motion sensor, which means for pacing a heart is connected to said motion sensor.

Abstract

The invention relates to an implantable motion sensor for measuring a patient's activity level comprising a fluid-tight, bio-compatible housing, a plurality of electrodes being coupled to the housing, the housing comprising a fluid that the fluid comprises at least one anisotropic molecule, the anisotropic properties of which are changed in relation to the motion of the fluid, whereby the state of the anisotropic molecules of the fluid is detectable by the electrodes. Hereby, the only moving part of the sensor is the anisotropic fluid. Hence, the sensor can be made very small.

Furthermore, the invention relates to an implantable cardiac pacemaker comprising the motion sensor of the invention.

(Fig. 1)

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
219




Fig. 1

3




Fig. 2